

Smart [PRO] 2.0 is the ideal solution for efficient lighting and relamping of indoor and out door sports facilities and large areas. The new range includes LED floodlights able to replace traditional sources from 250W to 1000W HID, with a luminous flux up to 38,000lm.

The exclusive features of Smart [PRO] 2.0



Modular

Smart [PR0] 2.0 is designed to adapt to different applications and installation needs, with a wide choice of various light and optic packages.



High performance

Smart [PRO] 2.0 great performance comes from a range of several, fundamental choices such us the use of latest-generation LEDs and the mechanical studies carefully carried out once designing the system.



Efficient

Compact design and installation ease, together with dimmering options available on request (1-10V and DALI), enable energy optimisation.

Smart [PR0] 2.0 is the best solution for new and relamping projects of indoor and outdoor sport facilities.



Reliable

The Italian design and the careful selection of materials ensure total reliability, stability and solidity for all Smart [PRO] 2.0 solutions.




















Dimensional drawings







Discover the full Smart [PRO] 2.0 range on www.gewiss.com

Technical characteristics

- Ta from -25°C to +50°C
- Lifespan: L80B10 > 100,000h
- Overvoltage protection >6KV

Application areas

Outdoor application areas

- High masts
- Airports and hangars
- Street intersections
- · Freight terminal stocking areas
- · Outdoor parking areas

Indoor and outdoor sports facilities

- Stadiums
- Football fields
- · Volleyball, basketball and tennis courts
- School gyms

Technical plus











Available optics

